



Technical Details

Style

Rangehood Type:	Fixed
Category Size:	60cm

Functionality

Extraction Type:	Ducted or Front Recirculating
Extraction Rate:	333m ³ /hr Net 440m ³ /hr Gross
Number of Motors:	2
Watts of Motor:	100w
Speeds:	3
Filtration:	2 x Aluminium Mesh
Lights:	1 x 2W LED
dBA Rating:	48-56dBA

Accessories

Charcoal Filter:	Optional (ORCF110 x 2)
------------------	------------------------


Installation

Maximum Current:	3 Pin Plug
Connection:	220 - 240V, 50Hz
Installation Type:	Built-in to Overhead Cabinetry

Warranty:	24 Months Parts & Labour
-----------	--------------------------

Dimensions/Weight

Overall Dimensions (mm):	150(h) x 600(w) x 500(d)
Flue Diameter (mm):	120mm
Weight:	7.5kg



Aesthetics

Finish:	Brushed Stainless Steel
Controls:	Push Buttons

Key Features



Front Recirculation

Sometimes it's not possible to duct your rangehood. If that's the case, then it's likely you'll need a recirculating Omega hood. These cleverly designed appliances draw the grease laden smoke and steam air inside the unit before cleaning and purify it — then sending it back as fresh air through the front panel. And, because there's no ducting, you can be up and running in no time.



Washable Filter

The removable, washable filter is easy to maintain and keep clean ensuring your rangehood always performs well.



Shallow Height

This rangehood has a shallow height meaning it is perfect for an areas with low overhead cupboards plus at only 60cm wide means it is perfect for smaller cooktops and spaces.

Customer Care

T: 1300 11 4357
E: sales@residentiagroup.com.au

NB: Drawings are not to scale - they are to assist only.
WARNING: technical specifications and product sizes can be varied by the manufacturer without notice. Cutouts for appliances should only be by physical product measurements.
The above information is indicative only.